



SYSTEM DESCRIPTION

The model PL-3 Lighting Loader® and corresponding body are mounted on a steel skid, built to fit cable-style roll-offs. Heavy steel rollers on the rear of the body allow for easy installation and removal, while the skid itself hydraulically locks to the chassis.

Both an 18 foot, 24 cubic yard body, and a 20 foot, 26 cubic yard body are available.

CONTROL OPTIONS

Dual manual controls for outriggers and loader on both sides of the truck for accessibility and visibility come standard. QUADSTICK® mechanically linked joystick controls are also an available option.

The PL-3 comes equipped with a grip strut serrated steel walk platform, steel handrails, and a frame lock control lever at the valve bank.

GENERAL SPECIFICATIONS

| | |
|------------------------|--------------|
| Reach | 20 ft. 7 in. |
| • Main Boom & Tip Boom | 16 ft. 7 in. |
| • Tip Extension | 4 ft. |
| Unit Weight (empty) | 11,500 lbs. |
| Outrigger Span | 11 ft. 8 in. |

LIFT CAPACITY

| Radius | Load Capacity |
|---------------|---------------|
| 10 ft. radius | 7,100 lbs. |
| 16 ft. radius | 4,400 lbs. |
| 20 ft. radius | 3,200 lbs. |

CHASSIS & HOIST REQUIREMENTS

| | 18 ft. 24 cy. | 20 ft. 26 cy. |
|-----------------|-----------------|-----------------|
| GVW | 60,000 (tandem) | 60,000 (tandem) |
| Cab to Trunnion | 174 in. | 194 in. |
| Hoist Capacity | 50,000 lbs. | 50,000 lbs. |
| Rail Length | 22 ft. 6 in. | 24 ft. 6 in. |

SCAN TO
LEARN MORE



4000 SR 60 West
Lake Wales, FL 33859
1.800.930.LOAD (5623)



PETERSENIND.COM
Contact Us Today To Learn More